

SonoDAQ & OpenTest

Next Generation

Intelligent Acoustic and Vibration Testing System



Precisely capture every data point to empower scientific and industrial innovation.



SonoDAQ

Next Generation Sound & Vibration DAQ

- Rugged carbon fiber mainframe with IP67
 protection
- Hot-swappable dual lithium batteries
- Gigabit Ethernet supporting daisy chaining and
 90 W PoE
- Modular design for 1000+ channels
- PTP synchronization with sampling accuracy better than 100 ns
- 170 dB dynamic range
- 1000V electrical isolation between slot
- Built-in AI and real-time edge computing
- · Local data recording on microSD card















Typical Applications









Product Features



High-Precision Performance

- Sampling rate up to 384 kS/s, 32-bit resolution
- Dual-gain ADC synchronous sampling with seamless data integration, achieving a dynamic range of 170 dB

口

Technological Innovation

- Proprietary multi-channel synchronous sampling technology: channel-to-channel skew < 100 ns
- Intelligent caching algorithm to prevent loss of high-frequency data
- Supports hot-swappable dual lithium batteries



User-Friendly Design

- · Plug-and-play on Windows, Linux, and macOS; full SDK included
- Accompanying data visualization software, supporting real-time waveform display and offline analysis



Reliability Assurance

Industrial-grade protection standard: IP67, operating temperature range: -40°C to 70°C



Mainframe Technical Specifications







SonoDAQ LT	SonoDAQ Pro	SonoDAQ Ultra		
System Configuration	System Configuration System Configuration			
24 Channels	Over 1000 Channels	Over 1000 Channels		
1	PTP (IEEE 1588v2)	PTP (IEEE 1588v2)		
1	AI & Edge Computing	Al & Edge Computing		
6 Modules	6 Modules	6 Modules		
Dual Ethernet	Daisy Chain Ethernet + PoE	Daisy Chain Ethernet + PoE		
/	External microSD Card Storage:	External microSD Card Storage:		
,	Default 256 GB, Optional Up to 2 TB	Default 256 GB, Optional Up to 2TB		
/	GPS & BDS / Wi-Fi	GPS & BDS / Wi-Fi		
Operating Temperature: -10 °C to 50 °C	Operating Temperature: -10 °C to 50 °C	Operating Temperature: -40 °C to 70 °C		
Vibration, Shock: EN60068-2	Vibration, Shock: EN60068-2	Vibration, Shock: GJB 150		
1000 V Slot Isolation	1000 V Slot Isolation 1000 V Slot Isolation			
IP43	IP43	IP67		

Module Technical Specifications









Analog Out	Analog Out - High			
Analog Output Mode	Amplifier Mode	Analog Output Mode 2 Channels, BNC 32-bit Resolution		
2 Channels, BNC	2 Channels, BNC, Class D Amplifier			
32-bit Resolution	Output Impedance: 190 mΩ			
204.8 kHz / 192 kHz Sampling Rate	Minimum Load: 4 Ω	204.8 kHz / 384 kHz Sampling Rate Output Voltage: 0 – 26.66 Vrms (75.4 Vpp) Balanced Mode 0 – 13.33 Vrms (37.7 Vpp) Unbalanced Mode		
Output Voltage: 0 – 21.21 Vrms (60 Vpp) Balanced Mode 0 – 10.61 Vrms (30 Vpp) Unbalanced Mode	Output Voltage: 9.475 Vrms (8 Ω load)			
Frequency Range: 0.1 Hz – 160 kHz	Supported Output Power: 10 W @ <0.2% THD+N (8 Ω load) 6 W @ <0.3% THD+N (4 Ω load) TEDS	Frequency Range: 5 Hz – 180 kHz Amplitude Accuracy: ±0.04 dB		
Amplitude Accuracy: ±0.03 dB	Noise Floor: ≤ -80 dBV			
Frequency Accuracy: ±0.0003% + 100 uHz	Impedance Measurement Range: $4~\Omega - 600~\Omega$	Frequency Accuracy: ±0.0003% + 100 uHz		
Crosstalk: ≤ (-147dB + 0.2 μV) to 20 kHz	Impedance Measurement Accuracy: ≤ 0.5% (20 Hz – 20 kHz)	Crosstalk: ≤ (-147 dB + 0.2 μ V) to 20 kHz		

In Planning

In Planning


NO.	M	1odule	Features	NO.	Module		Features
1	Bluetooth	Paulo O	2 × SMA Bluetooth 5.3	7	HDMI	HALL OF THE PROPERTY OF THE PR	2 × HDMI Audio In and Out
2	LE Audio	Double O	Bluetooth Low Energy	8	DSIO (Digital Serial IO)	DE	I2S / TDM
3	A2B		4 × Phoenix Terminal	9	Battery Module		12.6V / 6600mAH
4	PDM		3 × PDM	10	STG	DO	8 × Strain Gauge
5	LVI Module		8 × Logic Voltage / Tacho	11	ТНІ		8 × Thermocouple
6	CHG		4 × Charge Input	12			More






A new acoustic measurement software Revolutionize acoustic measuring with openness, Al, and universal compatibility

Q www.opentest.com







Al Meets Testing



Multi-Device Syncing



Cross-Platform



No-Code Development



Flexible Deployment





Enterprise-Grade Security



Manage Multi-Brand Hardware Under One Platform

OpenTest delivers cross-platform compatibility across professional-grade interfaces, consumer audio devices, and embedded systems, providing centralized control of multivendor hardware to eliminate driver conflicts and streamline workflows.





Pluggable Architecture

- Pre-Built Models
- Custom Al Model Training
- Support for Python/LabVIEW/MATLAB Algorithm Integration
- Complete API for Students to Write Personalized Testing Logic
- One-Stop Signal Acquisition and Custom Algorithm Processing

Adaptive Orchestration Framework

No-Code Workflows

Drag-and-drop interface to design test sequences (e.g., signal generation \rightarrow data capture \rightarrow Al analysis \rightarrow report generation).

Code-Friendly

Call Python, MATLAB, LabVIEW scripts or REST APIs for custom logic.



Industry Solutions



Consumer Electronics

Al-powered defect detection for TWS earbuds, speaker performance validation, etc.



Industrial Diagnostics

Predictive maintenance 2.0, smart production line QC, etc.



Research & Innovation

Acoustic material R&D, 3D noise mapping, etc.




Automotive Engineering

Full-vehicle NVH (noise, vibration, harshness) profiling



Features



Monitors & Meters


Dynamic Tracking and Instant Anomaly Detection

Continuous waveform monitoring and FFT spectrum analysis enable real-time identification of signal anomalies, such as clipping, clock jitter, and other issues. It simultaneously tracks key metrics, including RMS level, THD, SND, and frequency response, with configurable high-pass/low-pass filters and A/C/Z frequency weighting.

Continuous Sweep Analysis

Full-Range Rapid Measurement


This function utilizes logarithmically varying sweep signals to extend energy accumulation time in lowfrequency ranges, ensuring measurement accuracy. At the same time, it significantly improves test efficiency. It enables fast and reliable testing for applications such as resonance peak detection in speakers, phase continuity analysis in headphones, and frequency response flatness evaluation in amplifiers. Results automatically comply with industry standards and generate professional test reports. It is an indispensable tool for audio R&D, production, and quality control.



Sound Power Testing

Precise Quantification of Acoustic Performance

This solution supports sound pressure-based sound power measurement, fully compliant with international standards ISO 3744 (Engineering Method), ISO 3745 (Precision Method), and ISO 3746 (Survey Method), meeting various accuracy requirements in different scenarios. It is suitable for R&D and quality control in consumer electronics, automotive audio systems, and professional audio equipment.





Lightweight & Easy Deployment

Cross-Platform Compatibility (Windows/Linux/MacOS) Multi-Language Support (Python/LabVIEW/MATLAB)

To learn more, please visit www.opentest.com

